

High Duty Lathe Machine :



| | |
|--|--|
| Type of bed | Flat & V (Gap Bed) |
| Length of bed | 3660mm |
| Width of bed | 324mm |
| Height of center | 254mm |
| Swing over bed | 455mm |
| Admit between centre | 2490mm |
| Swing over cross slide | 255mm |
| Swing in gap | 725mm |
| No. of spindle speed | 8/30 to 495 rpm |
| Trading range | 2 to 24tpi |
| Spindle bore | 54mm |
| Tail stock spindle travel | 175 |
| Tail stock taper | Mt-4 |
| Stand. Accessories : ⌚ Chuck Plate ⌚ Gear Set ⌚ Centre Adaptor ⌚ Dead Centres ⌚ Dial Indicator ⌚ Square Tool Post ⌚ Tool Post Key | Optional Accessories : ⌚ Steady Rest ⌚ Follow Rest ⌚ Face Plate ⌚ Electrical Fitting ⌚ True Chuck & Dog Chuck ⌚ Quick Change Tool Post ⌚ Tapper Turning Attachment |

| | | |
|--|---|--------------------------------------|
| | ⌚ | Coolant Pump with Tank & Fittings |
| | ⌚ | Machine Lamp |
| | ⌚ | Rear Tool Post |
| | ⌚ | Norton Gear Box |
| | ⌚ | Key Way Attachment |
| | ⌚ | Tool Post Grinder |