

Power Press :



Power press C Type :

Tonnage	3	5	10	10	20	20	30	30	50	50	75	100	150	200	250
Crank Shaft Diameter	38	51	60	60	76	76	83	83	105	105	121	134	152	158	165
Stroke Length	25	25	25	51	51	76	63	76	76	102	115	127	152	158	165
Stroke Adjustment	6-25	6-25	6-25	6-51	13-51	13-76	13-63	13-76	13-76	13-102	13-115	13-127	13-152	13-158	13-165
Bed Size	203×152	205×178	381×255	381×255	508×305	508×305	558×356	558×356	750×520	750×520	863×596	914×635	965×685	1016×738	1016×778
Distance Bed TO Ram	127	153	205	205	280	280	292	292	406	406	483	483	495	519	544
Hole in Ram	19	25	25	25	32	32	38	38	38	38	45	51	57	63	63
Hole in Bed	51	63	76	76	83	83	89	89	127	127	152	178	191	216	229
Fly Wheel Diameter	330	405	435	435	550	550	660	660	810	810	910	1016	1118	1150	1320
Motor H.P. Required	0.5	0.5	1	1	2	2	3	3	5	5	7.5	10	15	20	25
Length	625	940	1100	1100	1240	1240	1325	1325	1575	1575	1760	1850	1970	2190	2340
Width	610	915	1070	1070	1220	1220	1300	1300	1510	1510	1700	1825	1900	2050	2230
Height	1016	1370	1525	1525	1830	1830	1920	1920	2420	2420	2950	3050	3200	3250	3300
Weight Approx Kgs.	150	275	525	525	1020	1020	1350	1350	2750	2750	4300	5500	6600	9000	11500

